

SCHOTTKY DIODES


FEATURES

Fast Switching Speed


For General Purpose Switching Applications

High Conductance


MARKING




MMBD4148A:5H



MMBD4148CA:D6



MMBD4148CC:D5



MMBD4148SE:D4



SOT-23

MAXIMUM RATINGS (TA=25°C unless otherwise noted)

Paramet	Symbol	Limits	Unit
Non-Repetitive Peak reverse voltage	V _{RM}	100	V
Peak Repetitive Peak reverse voltage	V _{RRM}		
Working Peak Reverse Voltage	V _{RWM}	100	V
RMS Reverse Voltage	V _{R(RMS)}	53	V
Forward Continuous Current	I _{FM}	300	mA
Average Rectified Output Current	I _O	200	mA
Peak forward surge current @=1.0μs @=1.0	I	2.0 1.0	A
Power Dissipation	P _D	350	mW
Thermal Resistance Junction to Ambient	R _{JA}	357	°C/W
Junction temperature	T _j	150	°C
Storage temperature	T _{STG}	-65~+150	°C

Electrical Ratings @TA=25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Reverse Breakdown Voltage	V _{(BR)R1}	100			V	I _R =100μA
	V _{(BR)R2}	75			V	I _R =5μA
Forward voltage	V _F			1	V	I _F =10mA
Reverse current	I _{R1}			5	μA	V _R =75V
	I _{R2}			25	nA	V _R =25V
Capacitance between terminals	C _T			4	pF	V _R =0V,f=1MHz
Reverse Recovery Time	t _{rr}			4	ns	I _F =I _R =10mA, V _R =6V,I _{rr} =0.1XI _R ,R _L =100

Typical Characteristics




Fig. 1 Power Derating Curve




Fig. 2 Forward Characteristics




Fig. 3 Typical Reverse Characteristics




Fig. 4 Typical Capacitance vs. Reverse Voltage